







DIMENSIONI (mm)				
Conduttori Sez. mm <sup>2</sup>	N° conduttori max.	Ø cavo interno min-max	Øcavo esterno min-max	Grandezza pressacavo NPT
16,0	1	5-13	8-18	1/2"
	2	11-18	17-25	3/4"
	4	17-24	23-32	1"
	5	23-30	29-39	1 1/4"
25,0	1	5-13	8-18	1/2"
	1	11-18	17-25	3/4"
	3	17-24	23-32	1"
	5	23-30	29-39	1 1/4"
35,0	1	5-13	8-18	1/2"
	1	11-18	17-25	3/4"
	3	17-24	23-32	1"
	5	23-30	29-39	1 1/4"
50,0	1	11-18	17-25	3/4"
	1	17-24	23-32	1"
	3	23-30	29-39	1 1/4"
	4	29-38	36-46	1 1/2"
	5	36-49	44-60	2"
70,0	1	11-18	17-25	3/4"
	1	17-24	23-32	1"
	2	23-30	29-39	1 1/4"
	4	29-38	36-46	1 1/2"
	5	36-49	44-60	2"
95,0	1	17-24	23-32	1"
	1	23-30	29-39	1 1/4"
	2	29-38	36-46	1 1/2"
	5	36-49	44-60	2"
120,0	1	17-24	23-32	1"
	1	23-30	29-39	1 1/4"
	1	29-38	36-46	1 1/2"
	4	36-49	44-60	2"
150,0	1	17-24	23-32	1"
	1	23-30	29-39	1 1/4"
	1	29-38	36-46	1 1/2"
	3	36-49	44-60	2"
	4	44-61	51-70	2 1/2"
185,0	1	23-30	29-39	1 1/4"
	1	29-38	36-46	1 1/2"
	1	36-49	44-60	2"
	4	44-61	51-70	2 1/2"
240,0	1	23-30	29-39	1 1/4"
	1	29-38	36-46	1 1/2"
	1	36-49	44-60	2"
	3	44-61	51-70	2 1/2"
	4	59-74	65-84	3"
300,0	1	29-38	36-46	1 1/2"
	1	36-49	44-60	2"
	1	44-61	51-70	2 1/2"
	4	59-74	65-84	3"
400,0	1	23-30	29-39	1 1/4"
	1	29-38	36-46	1 1/2"
	1	36-49	44-60	2"
	1	44-61	51-70	2 1/2"
500,0	1	29-37,5	36-46	1 1/2"
	1	36-48,5	44-60	2"
	1	44-61	51-70	2 1/2"
630,0	1	29-38	36-46	1 1/2"
	1	36-49	44-60	2"
	1	44-61	51-70	2 1/2"